



Parquet Varnish Hydro

Water Based Parquet Varnish

Parquet Primer Hydro

Transparent Water Based Primer for Parquet Varnishes



New
Technology
PU



www.vechro.gr



- ✓ Complete coverage of wood pores
- ✓ Easy rubbing
- ✓ Quick drying
- ✓ Strong adhesion

Parquet Primer Hydro

Transparent Water Based Primer for Parquet Varnishes

PARQUET PRIMER HYDRO is a water based primer specially designed for wooden surfaces. Due to its special composition. It provides strong adhesion and elasticity and fully covers wood pores by adjusting its absorbency. PARQUET PRIMER HYDRO dries quickly, it is easily rubbed and applied.



New technology PU

- ✓ Resistance to natural damage
- ✓ Quick drying
- ✓ Elasticity & hardness

Parquet Varnish Hydro

Water parquet Varnish

PARQUET VARNISH HYDRO is a transparent water based parquet varnish , ideal for new and old wooden parquets. It brings out the natural beauty of wooden surfaces, without flaking or cracking. It is easily applied and dries quickly. Due to its special composition, the formed surface combines both the hardness of the film - offering great resistance to all kinds of damage and water - and its elasticity, following the natural movements and grain of wood.



Application Instructions

1



Sandpaper well before application and clean the parquet surface of any dust.

2



Stir the can well before using it.

3



Apply Parquet Primer Hydro using a brush for the rest of the surface, one or two coats, depending on wood absorbency.

4



Sandpaper to completely cover wood pores and then clean the parquet well of any dust.

5



Apply the water varnish Parquet Varnish Hydro in two to three layers following the wood grain by using a brush for the “cuts” and a roller brush for the rest of the parquet surfaces.

6



The parquet is walkable after 24 hours. Careful use in the next two weeks is recommended.

Useful Advice



- ▶ Priming with Parquet Primer Hydro completely covers the wood pores, it prevents from flaking and cracking caused by the wood's distention and contraction, achieving at the same time strong adhesion of the Parquet Varnish Hydro.
- ▶ During the application and the drying procedure, the place should be firmly closed.
- ▶ Estimated drying times:
 - Recoating by Parquet Primer Hydro: 2-4 hours depending on the weather conditions.
 - Recoating by Parquet Varnish Hydro: 4-8 hours depending on the weather conditions.
- ▶ Mohair rollers are more suitable to use for excellent application of the varnish.
- ▶ Always apply the varnish following wood grain.
- ▶ Sandpaper after every layer.
- ▶ Parquet Varnish Hydro is walkable after 24 hours. For the next two weeks, until the film is completely hardened, the wooden surface should be used with caution.
- ▶ To preserve your parquet in excellent condition use special adhesive baizes under furniture and often clean the surface by using a wet cloth.

