



# DIAVROTIKO



## PAINT REMOVER

### GENERAL CHARACTERISTICS

It is suitable to remove old coatings from painted surfaces. Without methylene chloride.

### PHYSICAL PROPERTIES

<b>Specific gravity</b>	: 0,96 – 1,0 kg/lit
<b>Dilution</b>	: Ready for use
<b>Drying</b>	: 10-30 minute depending on weather conditions
<b>Covering power</b>	: 2-4 m <sup>2</sup> /lit depending on the surface and coating itself.

### APPLICATION

Apply PAINT REMOVER on the surface. It needs about 10-20 min to penetrate well into old paint. Afterwards the paints should be cropped. Repeat in case of non-effective results. In case of old paints and varnishes (especially two component) apply the remover thickly in an even layer and leave for more time or/and combine mechanical removal with a spatula or paint scraper. After use, clean with water and leave for drying before painting.

### APPLICATION CONDITIONS

Avoid use the material in high temperature, due to high evaporation ratio. The result will not be good. Open the can carefully. The remover may affect plastic surfaces.

### SAFETY INSTRUCTIONS

- Keep out of the reach of children
- Use only in well-ventilated areas.

### LABELLING \*

- **HIGHLY FLAMMABLE**
- *Contains Dimethoxymethane and methanol*

✱ **More information in Material Safety Data Sheets (MSDS).**