



## OXIDOL ALUMINIUM GALVANIZE

Special Anticorrosive Primer for non ferrous surfaces



**Covering Power:** 12 -14 m<sup>2</sup>/lt



**Drying:** 2 hours



**Dilution:** up to 4% if applied with brush or roller, or up to 6% if applied with spraygun, on volume with Thinner No1 of VECHRO



**Recoatability:** 12 - 16 hours



**Packing:** 750ml, 2,5lt

**Application:** Brush, Roller, Spraygun

### GENERAL CHARACTERISTICS

Special one component primer for preparing nonferrous surfaces such as aluminum, galvanized sheet iron, copper, in order to achieve very good adhesion of the finish coat.

### TECHNICAL CHARACTERISTICS

Texture	Velvet 5-8 units in 60°.
Specific weight	1,32 - 1,36 kg/lt.
Covering power	12 -14 m <sup>2</sup> /lt per layer.
Dilution	For application by brush or roller up to 4% on volume and for spray application use up to 6% on volume with No1 thinner of VECHRO.
Drying	Touch free in 2 hours.
Recoatability	Recoat able 12-16 hours after application. These times prolong under cold and wet weather conditions. These times prolong under cold and wet weather conditions.
VOC class	“One-pack performance coatings. Anticorrosive finishes” Type SB. VOC limit =500 gr/lt. Max VOC of product ready for use= 475 gr/lt. VOC: organic volatile compounds with boiling point < 250°C.
Adhesion	Excellent adhesion (GT0 - GT1).
Elasticity	Very good elasticity (Great Resistance to bending 180° on a rod diameter 3mm without cracking or flaking)
Shades	Light grey.



## SURFACE PREPARATION

Remove grease, oil, unsound existing paint, rust, dust and then clean thoroughly by using sandpaper.

## APPLICATION EQUIPMENT

Brush, roller, airless spray.

## APPLICATION

Stir well. Apply one coat OXIDOL ALUMINIUM GALVANISE. Sand with the proper sand paper and then apply GUMILAK metal.

## CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with thinner, water and soap.

## APPLICATION CONDITIONS

Temperature 8-30 OC and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

## STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

## LABELLING

More information in Material Safety Data Sheets (MSDS).

## SAFETY

Read the tag on the back side of the product. Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.