



Oxidol Minio

Superior Anticorrosive Primer



Covering Power: 13-15 m²/lt



Drying: 1½ - 2 hours. Fully dry in 3 - 4 hours.



Dilution: Up to 5% on volume with White Spirit using brush/roller, or up to 20% with Thinner No1 when using spraygun



Recoatability: 10- 16 hours



Packing: 750ml, 2,5lt



Application: Brush, Roller, Spraygun

GENERAL CHARACTERISTICS

Superior anticorrosive primer MINIO type, with low VOC content. Gives excellent anticorrosive protection to ferrous surfaces even in strong corrosive conditions and very good adhesion. It doesn't contain toxic anticorrosive pigments. Easy to apply with very good leveling. Quick drying.

TECHNICAL CHARACTERISTICS

Texture	Satin 14-20 units in 60°.
Specific weight	1,33 - 1,38 kg/lt.
Covering power	13 -15 m ² /lt per layer.
Dilution	Up to 5% on volume with Smaltolux White SPIRIT for application by brush or roller and for spray application use up to 18% on volume with No1 thinner of VECHRO.
Drying	1½ - 2 hours touch free. Drying through 3-4 hours.
Recoatability	Recoatible 10-16 hours after application or after first layer's hardening. These times prolong under cold and wet weather conditions.
VOC class	" One-pack performance coatings. Primer for ferrous substrates" Type SB. VOC limit = 500 gr/lt. Max VOC of product ready for use= 450 gr/lt. VOC: organic volatile compounds with boiling point < 250°C.
Shades	Orange.



SURFACE PREPARATION

Sandpaper well and clean the surface of dust, oil, cropped paints, and dampness.

APPLICATION

Stir well. Apply one or two coats Oxidol Minio. For better protection, primed surfaces should be painted with the suitable finish paint such as Gumilak metal, Smaltolux extra, Smaltolux hydro or any enamel paint from VECHRO.

CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with thinner, hot water and soap.

APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

LABELLING

More information in Material Safety Data Sheets (MSDS).

SAFETY

Read the tag on the back side of the product. Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.