



Smaltox Mono

Special Stain blocking primer



Covering Power: 8 - 10 m²/lt



Drying: 1 - 2 hours



Dilution: up to 5% in volume with Smaltolux White Spirit



Recoatability: 2 - 4 hours



Packing: 750ml, 2,5lt

Application: Brush, Roller

GENERAL CHARACTERISTICS

White primer based on acrylic resins with low VOC content suitable for interior and exterior use. Ideal as stain blocking primer with excellent blocking properties against nicotine, smoke, urban pollution, markers, graffiti, mould, old dampness. Excellent adhesion to new renders and cement surfaces and very good consolidation of old surfaces like lime, gypsum, old concrete, old damaged painted surfaces. Ideal for the priming and renovation of already painted exterior surfaces. Very good hiding which helps to spent less finish coat. Quick drying. It can be used as undercoat for emulsion or acrylic paints.

TECHNICAL CHARACTERISTICS

Texture	Mat.
Special Weight	1,41 - 1,44 kg/lt.
Covering Power	8-10 m ² /lt per coat depending on the surface
Dilution	As "Blocking Primer" for application by brush or roller up to 5% on volume with SMALTOLUX WHITE SPIRIT. As "Binding Primer" for application by brush or roller up to 50% on volume with SMALTOLUX WHITE SPIRIT.
Drying	Touch dry after 1-2 hours.
Recoatability	Recoat after 2-4 hours. These times prolong under cold and wet conditions.
VOC Class	a. "Blocking Primers" Type SB. VOC limit =450 gr/lt. Max VOC of product ready for use= 440 gr/lt. b. "Binding Primers" Type SB. VOC limit =750 gr/lt. Max VOC of product ready for use= 550 gr/lt. It fulfills the requirements of E.C. legislation till 2011. VOC: organic volatile compounds with boiling point < 250°C.
Shades	White. Avoid tinting.



SURFACE PREPARATION

Clean the surface of dust, oil, cropped paints and dampness. Carefully remove dust with sandpaper.

APPLICATION

Stir well before use. Apply one or two coats of SMALTOX mono. After priming use SMALTOPLAST ACRYLIC 100%, SMALTOPLAST extra or any emulsion or acrylic paint from VECHRO.

CLEANNING TOOLS

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with warm water and soap.

APPLICATION CONDITIONS

Temperature 8-30°C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality. New concretes or masonry should be dried for a period of 3-4 weeks before priming.

STORAGE

Close well after use. Store in a cool place. Protect from sun exposure.

LABELLING

For more information please ask for the product's Safety Data Sheet (MSDS).

SAFETY

Read instructions on back side of the product. Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.