



## Smaltox Water Stop

Water-based waterproofing primer



**Covering Power:** 11-13 m<sup>2</sup>/lt



**Drying:** ½ - 1 hour



**Dilution:** 8-15% on volume with water



**Recoatability:** 3 - 4 hours



**Packing:** 750ml, 2,5lt



**Application:** Brush, Roller, Spraygun

### GENERAL CHARACTERISTICS

Water based low odor and low VOC masonry waterproofing primer. Suitable for priming interior and exterior masonry surfaces above or underground level. The solution for water seepage, humidity and efflorescence problems. Ideal primer for renovation of places where humidity and alkali spots are not preferable. Excellent adhesion and alkali resistance, very good hiding. Quick drying and recoat able with indoor emulsion paints and outdoor acrylics.

### TECHNICAL CHARACTERISTICS

<b>Texture</b>	Mat.
<b>Specific weight</b>	1,38 - 1,42 kg/lt .
<b>Covering power</b>	11 -13 m <sup>2</sup> /lt per layer
<b>Dilution</b>	8 - 15% on volume with water.
<b>Drying</b>	½ - 1 hour touch free.
<b>Recoatability</b>	Recoatable after 3-4 hours. These times prolong under cold and wet conditions.
<b>VOC class</b>	"Blocking Primers". Type WB. VOC limit=30gr/lt. Max VOC of product ready for use = 5gr/lt.
<b>Shades</b>	Light Grey.



## SURFACE PREPARATION

Clean the surface from oil, cropped paints, dust, dampness and moulds. In case of severe humidity or water seepage problems, look for other repair methods, before priming with Smaltox Water Stop.

## APPLICATION EQUIPMENT

Brush, roller and airless spray.

## APPLICATION

Stir well before use. Apply uniformly on the surface 2 coats Smaltox Water Stop. Don't tint the product.

## CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with thinner, water and soap.

## APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality. New concretes or masonry should be dried for a period of 3-4 weeks before priming.

## STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

## LABELLING

No hazard labeling required according to National European legislation.

\* More information in Safety Data Sheets (SDS).

## SAFETY

Read the tag on the back side of the product. Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.