



Vinyflex

Flat Emulsion Paint



Covering Power: 10-12 m²/lt



Drying: 1 - 2 hours



Dilution: 5 - 10% with water



Recoatability: 3 - 5 hours



Packing: 3lt, 9lt, 15lt

Application: Brush, Roller, Spraygun

GENERAL CHARACTERISTICS

Water based emulsion paint. It can be used to paint new or old painted walls and ceilings, plasters and wood, gypsum board and concrete surfaces after their proper preparation. Its' great performance in addition with its low price make VINYFLEX ideal for professionals who ask for economic solution.

TECHNICAL CHARACTERISTICS

Texture	Flat with sheen up to 6-10 units at 85°.
Specific weight	1,53 - 1,57 kg/lt (white).
Covering power	10 - 12 m ² /lt per layer depending on the surface.
Dilution	5 - 10% on volume with water.
Drying	Dry to touch in 1 - 2 hours. The paint adopts full resistance in washing 3-4 weeks after application.
Recoatability	3-5 hours. These times could elongate under cold and wet weather conditions.
VOC class	"Interior matt coatings for walls and ceilings". Type WB. VOC limit = 30gr/lt. Max VOC of product ready for use = 20gr/lt. VOC: organic volatile compounds with boiling point < 250°C.
Shades	White.



SURFACE PREPARATION

Clean the surface of dust, oil, cropped old paints, dampness etc. Sandpaper well and prime with one coat of Smaltoplast Universal Primer or ACRYLIC PRIMER, while very dirty surfaces (damp, nicotine, ink, fungi, graffiti, oil spots etc) should be primed with special primer SMALTOX hydro.

APPLICATION

Stir well before use. Apply two coats VINYFLEX emulsion..

CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with thinner, water and soap.

APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

SAFETY

Read the tag on the back side of the product. Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.