



## Polydox Hydro

### Impregnated Stone Protective



**Covering Power:** 4 - 8 m<sup>2</sup>/lt



**Drying:** ½ - 1 hour



**Dilution:** ready to use



**Recoatability:** 1 - 2 hours



**Packing:** 750ml, 2,5lt

**Application:** Brush, Spraygun

### GENERAL CHARACTERISTICS

POLYDOX hydro is an odorless flat impregnated stone protective for exterior and interior use. Its unique synthesis guarantees for excellent penetration, water proofing and oil as also soil repellency.

It is suitable for porous building materials such as natural and artificial stone, brickwork, marble, cement, ceramics and other absorbent materials.

It does not create film; it does not yellow and it does not affect the appearance of the color shade of the treated material. Easy cleaned with resistance to fungi development.

It protects stone buildings from weather and atmospheric pollution. Product of applied nanotechnology.

### TECHNICAL CHARACTERISTICS

<b>Texture</b>	Flat, non-film forming.
<b>Specific weight</b>	0,98- 1,02 kg/lt.
<b>Covering power</b>	4-8 m <sup>2</sup> /lt per layer, depending on substrate porosity.
<b>Dilution</b>	Ready for use.
<b>Drying</b>	½-1 hours touch free.
<b>Recoatability</b>	Recoat able ½-1 hours after application and before the complete drying of the previous coating. These times prolong under cold and wet weather conditions. Warning! Avoid reapplying the day after!
<b>VOC class</b>	“One-pack performance / floor coating”. Type WB. VOC limit = 100 gr/lt. Max VOC of product ready for use = 5 gr/lt. VOC: organic volatile compounds with boiling point < 250½ °C.
<b>Shades</b>	Transparent milky white. Cannot be tinted.



## SURFACE PREPARATION

Clean the surface of dust, oil, grease, petrol, paraffin etc. The surfaces to be paint must be clean and absolutely dry.

## APPLICATION

Stir well before use. Apply POLYDOX hydro IMPREGNATION FLAT in such way in order the substrate absorb enough quantity. Avoid reapplying the day after.

## CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with thinner No1 of Vechro and water and soap.

## APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

## STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

## LABELLING

More information in Safety Data Sheets (MSDS).

## SAFETY

Read the tag on the back side of the product. Keep out of the reach of children.

The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.