



Vechro Pro Bondfix Quartz

Hybrid Quartz Adhesion Primer



Covering Power: 4 - 12 m²/lt



Drying: ½ - 1 hour



Dilution: 0%



Recoatability: 3 - 4 hours



Packing: 750ml, 2,5lt, 10lt

Application: Brush, Roller, Spraygun

GENERAL CHARACTERISTICS

Water based hybrid low odor and low VOC binding primer. It is used as bridge above cement, masonry, cement board, gypsum board, expanded or extruded polystyrene, porobeton, cement tile, ceramic tiles, mosaic, sea plywood, MDF and other wooden or metallic substrates for enhances the adhesion on them of plasters, tile adhesives, walk able cement screed, leveling compounds and other coherent materials. Can replace 1st coat coarse plasters. For indoor and outdoor use. Excellent adhesion, alkali and water resistance. After the application it offers a rough finish.

TECHNICAL CHARACTERISTICS

| | |
|------------------------|---|
| Texture | Rough surface. |
| Specific weight | 1,21 -1,25 g/l |
| Covering power | 4-12 m ² /lt per coat depending on the porosity of surface and film thickness required |
| Dilution | Ready for use. |
| Drying | Touch dry after ½-1 hour. |
| Recoatability | Recoatable after 3-4 hours. These times prolong under cold and wet conditions. |
| VOC class | "Binding Primers". Type WB. VOC limit=30gr/lt. Max VOC of product ready for use=25gr/lt. |
| Color shades | Yellow oxide. Avoid to use other colorants! |



SURFACE PREPARATION

Clean the surface from oil, cropped paints, dust, dampness and moulds.

APPLICATION

Stir well before use. Apply uniformly 1-2 coats Vechro Pro Bondfix Quartz on the surface in order to obtain the required texture effect and adherence properties.

CLEANING EQUIPMENT

Keep the tools wet during application. Strain well your tools from paint back to the pot and clean immediately with water and soap.

APPLICATION CONDITIONS

Temperature 8-30°C and relative humidity lower than 80%. Contrary weather conditions may degrade product's quality. New concretes or masonry should be dried for a period of 3-4 weeks before priming.

STORAGE

Close well after use. Store in a cool place. Protect from freezing and sun exposure.

LABELLING

More information in Safety Data Sheets (MSDS).

SAFETY

Read the tag on the back side of the product. Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.