



CHIEF ACRYLIC

100% Acrylic Paint



Covering Power: 9 - 11 m²/lt



Drying: 1 - 2 hours



Dilution: 5 - 15 % in volume with water



Recoatability: 4 - 6 hours



Packing: 750ml, 3lt, 9lt, 15lt

Shades : 1 lt, 3 lt, 9 lt



Application: Brush, Roller & airless spray

GENERAL CHARACTERISTICS

Mat 100% acrylic emulsion paint for exterior use, suitable for walls, plasters, concrete and gypsum board. Chief Acrylic has very good hiding and covering power. It is easy to apply with low odor and very good leveling.

Very good cost-effective solution for the professionals with excellent weather resistance.

TECHNICAL CHARACTERISTICS

Texture	Mat with sheen up to 6-10 units at 85°.
Special Weight	1,40 - 1,58 kg/lt.
Covering Power	9 - 11 m ² /lt. per layer, depending on the surface.
Dilution	5 - 15 % on volume with water.
Drying	Dry to touch in 1 - 2 hours. The paint adopts full resistance in washing 3-4 weeks after stain.
Recoatability	4-6 hours. These times prolong under cold and wet weather conditions.
VOC Class	“Exterior wall coatings of mineral substrate”. Type WB. VOC limit = 40 gr/lt. Max VOC of product ready for use = 20 gr/lt. VOC: organic volatile compounds with boiling point < 250°C.
Shades	White, Brown 503, PCM 2131, GREY 504, PCM 1854, and thousand shades via Vechro Tinting system.



SURFACE PREPARATION

Clean the surface of dust, oil, cropped paints and dampness. Sand-paper well and prime surfaces painted with white lime or new concretes with Smaltoplast Universal Primer, while very dirty surfaces (damp, nicotine, ink, fungi, graffiti, oil spots etc.) should be primed with special primer SMALTOX hydro or SMALTOX mono.

APPLICATION

Stir well before use. Apply uniformly 1 or 2 coats CHIEF ACRYLIC.

Hint! We reduce the total coat layers number of dark shades by applying **SMALTOX hydro** or CHIEF acrylic in gray S 1502-Y before applying dark yellow shades, S 1502-R red before applying dark red shades etc.

CLEANNING TOOLS

While working keep your equipment wet, either in the pot or in the paint launder. Strain well your tools from paint back to the pot and clean immediately with water and soap. Avoid washing materials entering into watercourses.

APPLICATION CONDITIONS

Temperature 8-30 0C and relative humidity lower than 80%. Contrary weather conditions may degrade product's quality. New concretes or masonry should be dried for a period of 3-4 weeks before priming.

STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

SAFETY

Read instructions on back side of the product. Keep out of the reach of children. No danger symbols according to EC legislation.

The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.

