



SMALTOLUX WHITE SPIRIT

THINNER FOR APPLICATION BY
BRUSH-ROLLER



Packaging: 375ml, 750ml, 4lt,
16lt or other upon request

Application: As solvents in thinners for
paints and varnishes for application by
brush or roller. Metal cleaning and
degreasing.

GENERAL CHARACTERISTICS

LOW AROMATIC WHITE SPIRITS are mixtures of paraffin, cycloparaffin and aromatic hydrocarbons with boiling range which lie between 160 - 200 °C. They are clear water -white liquids, chemically stable and non-corrosive and possess a mild odor.

TECHNICAL CHARACTERISTICS

Distillation range	IBP 160 °C
	DP 200 °C
Density at 15 °C	ASTM D1298 0,75-0,79 kg/lt
Flash point Abel	IP 1070 38 °C
	PMCC ASTM D93 -
Aniline point	ASTM D611 55 °C
Color	ASTM D156 Saybolt scale +30
Refractive index at 20°C	ASTM D1218 1434
Br Index	ASTM D1492 150 MgBr/100g
Evaporation rate (nBuAc=1.0)	ASTM D3539 0.10
Benzene	GC <100 mg/kg
Total aromatics	ASTM D1319 17.5 % vol
Viscosity at 25°C	ASTM D445 1.08 mm ² /s
Total sulfur	ASTM D3120 <5mg/kg



LABELLING

For more information please ask for the product's Safety Data Sheet (MSDS).

SAFETY

Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.