



SMALTOXYL DECO

PROTECTIVE and DECORATIVE WOOD
VARNISH



Covering Power: 9-11 m²/lt per coat, in already well-primed surface



Drying: 3 - 4 hours



Dilution: 5% on volume with thinner SMALTOLUX WHITE SPIRIT and 8% with thinner No1 of VECHRO for application by spray



Recoatability: 18-24 hours



Packaging: 200ml, 750ml, 2,5lt

Application: Brush, Roller, Spray-Gun

GENERAL CHARACTERISTICS

Protective and decorative varnish for wooden surfaces, based on modified alkyd resins. Suitable for internal and external use. It is recommended for roofs, wood made houses, frames of doors etc. It contains pigments of high transparency that its appearance stays natural, while at the same time it has great resistance in UV radiation. Due to its formula it protects the dried film against mildew growth and moisture. It has great covering power, is easy to work with and stains wonderful. Keeps elasticity in order to follow woods movements.

TECHNICAL CHARACTERISTICS

Texture	Gloss and satin.
Specific gravity	0,86-0,90 kg/lt (gloss) 0,96-0,98 kg/lt (satin)
Covering Power	9-11 m ² /lt per coat, in already well-primed surface
Dilution	5% on volume with thinner SMALTOLUX WHITE SPIRIT and 8% with thinner No1 of VECHRO for application by spray.
Drying	Dry to touch in 3 - 4 hours.
Recoatability	18-24 hours after application. Those times will be prolonged in cold and wet weather conditions.
VOC Class	"Interior/exterior trim varnishes and wood stains." Type SB. VOC limit =500 gr/lt. Max VOC of product ready for use= 485 gr/lt. VOC: organic volatile compounds with boiling point < 250°C.
Color shades	Gloss & Satin: Transparent- Colorless



SURFACE PREPARATION

Clean the surface of dust, oil, cropped paints or varnishes. Sandpaper well. On new surfaces, apply one or two coats of SMALTOXYL BASE for better protection from fungi and insects.

APPLICATION

Stir well till thinner is fully embodied. Apply two-three coats SMALTOXYL DECO.

CLEANNING TOOLS

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with thinner, water and soap.

APPLICATION CONDITIONS

Temperature 8-30°C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

STORAGE

Close well after use. Store in a cool place. Protect from sun exposure.

LABELLING

For more information please ask for the product's Safety Data Sheet (MSDS).

SAFETY

Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.