



Vechro Pro Acrylic Primer

Water based primer for internal & external use



Covering Power: 16 - 20 m²/lt



Drying: 1 - 1½ hours



Dilution: 50 - 300 % in volume with water



Recoatability: 4 - 6 hours



Packing: 750ml, 3lt, 10lt, 16,5lt

Application: Brush, Roller

GENERAL CHARACTERISTICS

Vechro Pro Acrylic Primer is water based, transparent acrylic primer with very good adhesion and penetration on cement surfaces, in comparison with other common acrylic primers. It is suitable for internal and external use and recoatable with any emulsion paint.

It gives great alkali resistance on alkaline surfaces such as concrete, plasters, asbestos etc. It could increase the covering power of the final paint because of reducing the absorbency of the surface. It is easy to work with.

TECHNICAL CHARACTERISTICS

Special Weight	1,02 - 1,04 kg/lt
Covering Power	16-20 m ² /lt per coat, depending on the surface absorbency.
Dilution	50 - 300% with water depending on the surface and its absorbency.
Drying	Touch free in 1 - 1 ½ hour.
Recoatability	4 - 6 hours. These times elongate under bad weather conditions.
VOC Class	"Binding primers". Type WB. VOC limit = 30gr/lt. Max VOC of product ready for use = 2gr/lt. It fulfills the requirements of E.C. legislation after 2011.VOC: organic volatile compounds with boiling point < 250°C.
Alkali, water resistance	ACRYLIC primer is water and alkali resistant.
Shades	Transparent Milky-white



SURFACE PREPARATION

To make sure of a successful adhesion, the surface has to be cleaned of dust, oil, cropped paints and dampness. Sandpaper well. New concretes should be dried for a period of 3-4 weeks before priming.

APPLICATION

Stir well before use. Apply uniformly one (or two coats if needed) Vechro Pro Acrylic Primer. After priming use Smaltoplast Acrylic 100%, Smaltoplast Extra or any emulsion or acrylic paint from Vechro.

CLEANING TOOLS

While working keep your equipment wet, either in the pot or in the paint launder. Strain well your tools from paint back to the pot and clean immediately with water and soap. Close well after use.

APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality. New concretes should be dried for a period of 3-4 weeks before priming.

STORAGE

Close well after use. Store in a cool place. Protect from sun exposure.

LABELLING

Vechro Pro Acrylic Primer needs no danger symbols according to EC legislation.

SAFETY

Read instructions on back side of the product. Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.