



Vinyflex Acrylic

Acrylic Emulsion Paint



Covering Power: 9-11 m²/lt



Drying: 1 - 2 hours



Dilution: 5 - 10% with water



Recoatability: 4 - 6 hours



Packing: 3lt, 9lt, 15lt



Application: Brush, Roller, Spraygun

GENERAL CHARACTERISTICS

Water based acrylic emulsion paint. It can be used to paint new or old painted walls, plasters, gypsum board and concrete surfaces if they are well prepared. It is ideal for frequent recoating combining economy with excellent application and levelling properties.

TECHNICAL CHARACTERISTICS

Texture	Mat with sheen up to 6-10 units at 85°.
Specific weight	1,46- 1,50 kg/lt.
Covering power	9-11 m ² /lt per layer depending on the surface.
Dilution	5-10% on volume with water.
Drying	1-2 hours touch free. The paint adopts full resistance in washing 3-4 weeks after stain.
Recoatability	Recoatable 4-6 hours after first layer's application. These times prolong under cold and wet weather conditions.
VOC class	"Exterior wall coatings of mineral substrate". Type WB. VOC limit = 40gr/lt. Max VOC of product ready for use = 20gr/lt. VOC: volatile organic compounds with boiling point < 2500C.
Shades	White.



SURFACE PREPARATION

Clean the surface of oil, cropped paints and dampness. Sandpaper well and remove dust. Painted surfaces or new concretes are primed with Smaltoplast Universal Primer or SMALTODUR primer. Dirty surfaces (nicotine, damp, smoke) should be primed with special primer SMALTOX hydro or SMALTOX mono.

APPLICATION

Stir well. Apply one or two coats VINYFLEX ACRYLIC.

CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with thinner, water and soap.

APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

LABELLING

VINYFLEX acrylic needs no danger symbols according to EC legislation.

SAFETY

Read the tag on the back side of the product. Keep out of the reach of children.



The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.