



VECHRO PRO Finish Filler



Covering Power: 1 - 2 m²/kg



Drying: 2 - 3 hours



Dilution: Ready to use



Recoatability: 4 - 6 hours



Packaging: 5kg, 18kg

Application: Spatula, Roller, Airless

GENERAL CHARACTERISTICS

It is a ready-to-use paste putty for interior surfaces, reinforced with acrylic resins, which achieves a smooth and durable finish.

It has excellent adhesion, ensuring a strong and durable bond that minimizes the risk of cracking or delamination over time. It has good filling and smoothing properties and effectively fills gaps, cracks or uneven surfaces, creating a smooth and uniform finish.

Reinforcement with acrylic resins gives it the ability to flex following the movement of the masonry substrate, minimizing the appearance of cracks and ensuring the longevity of the finish.

It has an easy application, as well as a smooth and manageable consistency, allowing for effortless, trouble-free application to the surface.

It has a fast-drying time, allowing for more efficient project completion and reducing downtime. Fast drying also facilitates timely execution of subsequent steps, such as sanding or painting.

Minimal shrinkage helps maintain the integrity of the applied putty layer, reducing the possibility of cracks or surface irregularities after drying. Low odor minimizes impact on indoor air quality and provides a more comfortable working environment during application.

TECHNICAL CHARACTERISTICS

Density	1,73 - 1,77 kg/lt
Covering Power	1 - 2 m ² /kg per layer depending on the thickness
Dilution	The putty is ready to use. Diluted with water if necessary depending on use
Drying	2 - 3 hours, depending on layer's thickness
Recoatability	Recoatable 4 - 6 hours after drying depending on temperature and humidity
Sanding	6 - 8 hours
Colour	White



VECHRO PRO Finish Filler



SURFACE PREPARATION

Clean the surface of dust, oil, cropped paints and dampness.

APPLICATION

The putty is ready for use. Diluted with water if necessary depending on use. It is applied with a spatula, roller or airless. Do not apply at temperatures below 5°C. Spread the putty evenly with the spatula. In case of roller or airless follows leveling with spatula. After it has thoroughly dry, sand and then prime with Smaltoplast Universal Primer or Pro Acrylic Primer.

CLEANNING TOOLS

Keep the tools wet and strain well from paint back to the pot. Clean immediately with water and soap.

APPLICATION CONDITIONS

Temperature 8-30°C and relative humidity lower than 80%. Adverse weather conditions during application may alter the final properties of the product.

STORAGE

After application, close the container tightly to keep it in good condition for future use. Store in a cool environment. Protect the material from frost and sun exposure. Minimum shelf life 12 months.

SAFETY

Read the label before use. For detailed instructions - precautions consult the Safety Data Sheet of the product.

CE	
www.vechro.gr	
EN 13963 – Type A3	
Jointing materials for gypsum boards	
Reaction to fire	A2-s1, d0
Flexural strength	≥ 149N

The technical data and instructions included in this technical leaflet are based on audits of confidential laboratories and result of the knowledge and experience of the company's scientific staff. The quality of the product is guaranteed by the company, which is aligned with the requirements of ISO 9001, 14001 and EMAS. As a producer, we are not responsible for any damage or damage caused if the product has not been used for proper application and in accordance with its instructions for use.